

# TG-BT-100

## PRODUCT INFORMATION

### INSULATION

- Minimizing heat loss thanks to the use of high-density polyurethane foam.

### UNIVERSALITY

- Ideal for use with all heat sources such as: heat pump, solar collectors, pellet stove, gas stove, coal stove, fireplace with water jacket, solid fuel stove, etc.
- Possibility of connecting an electric heater.

### MADE WITH ATTENTION TO EVERY DETAIL

- A stylish and modern design that can also serve as an attractive finishing element.



ENVIRONMENTALLY FRIENDLY



HYGIENIC PRODUCTS



COST SAVING



QUICK WATER HEATING



CORROSION RESISTANCE



## PRODUCT SPECIFICATIONS

| Model     | Weight [kg] | Dimensions (diameter /height) [mm] | Maximum operating temperature of the tank [°C] | Maximum allowable working pressure [bar] | Insulation                          | Tank material | Outer casing material           |
|-----------|-------------|------------------------------------|--|--|-------------------------------------|---------------|---------------------------------|
| TG-BT-100 | 22,5        | 480/1000                           | 95   | 6  | Polyurethane foam 50mm 50/kgm3 BASF | SUS304        | Galvanized steel, powder-coated |

## ENERGY LABEL

| Model     | Energy efficiency class | Heat loss [W] |
|-----------|-------------------------|---------------|
| TG-BT-100 | B                       | 48            |