

## TG-BT-500

### PRODUCT INFORMATION

#### INSULATION

- Minimizing heat loss thanks to the use of high-density polyurethane foam.

#### UNIVERSALITY

- Ideal for use with all heat sources such as: heat pump, solar collectors, pellet stove, gas stove, coal stove, fireplace with water jacket, solid fuel stove, etc.
- Possibility of connecting an electric heater.

#### MADE WITH ATTENTION TO EVERY DETAIL

- A stylish and modern design that can also serve as an attractive finishing element.



ENVIRONMENTALLY  
FRIENDLY



HYGIENIC  
PRODUCTS



COST  
SAVING



QUICK  
WATER  
HEATING



CORROSION  
RESISTANCE



### PRODUCT SPECIFICATIONS

| Model     | Weight [kg] | Dimensions<br>(diameter<br>/height)<br>[mm] | Maximum<br>operating<br>temperature<br>of the tank [°C] | Maximum<br>allowable<br>working<br>pressure [bar] | Insulation                                | Tank material | Outer casing<br>material           |
|-----------|-------------|---------------------------------------------|---------------------------------------------------------|---------------------------------------------------|-------------------------------------------|---------------|------------------------------------|
| TG-BT-500 | 79,0        | 700/1790                                    | 95                                                      | 6                                                 | Polyurethane<br>foam 50mm<br>50/kgm³ BASF | SUS304        | Galvanized steel,<br>powder-coated |

### ENERGY LABEL

| Model     | Energy efficiency class | Heat loss [W] |
|-----------|-------------------------|---------------|
| TG-BT-500 | B                       | 82            |