

TG-S-CWU-350-4

PRODUCT INFORMATION

A VERY LARGE SURFACE COIL

- Energy efficiency - tanks with such a large coil surface allow you to reduce the amount of energy used for heating water by up to 70%.
- Efficiency - extremely fast water heating.

INSULATION

- Minimizing heat loss thanks to the use of high-density polyurethane foam.

UNIVERSALITY

- Ideal for use with all heat sources such as: heat pump, solar collectors, pellet stove, gas stove, coal stove, fireplace with water jacket, solid fuel stove, etc.
- Possibility of connecting an electric heater.

MADE WITH ATTENTION TO EVERY DETAIL

- A stylish and modern design that can also serve as an attractive finishing element.



ENVIRONMENTALLY FRIENDLY



HYGIENIC PRODUCTS



COST SAVING



QUICK WATER HEATING



CORROSION RESISTANCE

PRODUCT SPECIFICATIONS

Model	Weight [kg]	Dimensions (diameter /height) [mm]	Maximum operating temperature of the tank [°C]	Maximum allowable working pressure [bar]	Insulation	Tank material	Outer casing material
TG-S-CWU-350-4	93	700/1348	95	6	Polyurethane foam 50mm 50/kgm³ BASF	SUS304	Galvanized steel, powder-oated

ENERGY LABEL

Model	Energy efficiency class	Heat loss [W]
TG-S-CWU-350-4	B	65

COIL PARAMETERS

Model	Heat exchanger surface area [m²]	Capacity [l]	Maximum operating temperature [°C]	Maximum allowable pressure [bar]
TG-S-CWU-350-4	4	18	95	5